




**NEW EASYNICHE™ SIZES AVAILABLE TO FIT WITH YOUR CHOICE OF TILE**

Start with your overall tile length to select the EasyNiche™ that will work best for your space. Standard thickness tiles will fit the recess size indicated.


**LARGE RECTANGLE**

OVERALL TILE LENGTH	RECESS SIZE (mm)	CODE
1500mm	1540 x 340	EN1500
1200mm	1240 x 340	EN1200
900mm	940 x 340	EN900
750mm	790 x 340	EN750




**SMALL RECTANGLE**

OVERALL TILE LENGTH	RECESS SIZE (mm)	CODE
600mm	640 x 340	EN600
500mm	540 x 340	EN500
450mm	490 x 340	EN450
350mm	390 x 340	EN350*
200mm	240 x 340	EN200*



**SQUARE**

OVERALL TILE LENGTH	RECESS SIZE (mm)	CODE
300mm	340 x 340	EN300*



**FOOTREST**

OVERALL TILE LENGTH	RECESS SIZE (mm)	CODE
140mm	180 x 120	EN140F*



\*Fits into 70mm wall cavity.

**SPECIFICATION**

- One-piece lightweight construction made from rigid GRP composite.
- 100% waterproof.
- Immediately ready-to-tile (once interlayer is applied).
- Built-in gradient prevents water ponding.
- Compliant with Australia Building Code and AS3740
- Fits into 90mm wall cavity.
- Some sizes available to suit 70mm wall cavity.\*
- Suitable for horizontal or vertical installation (except footrest).
- Suitable for all wallboards (recommended 6mm minimum).
- Supplied with self-adhesive reinforcement band for connection to wallboard and waterproofing.
- Compatible with compliant liquid membrane for full wall waterproofing.
- Must be installed prior to wallboard, and requires additional framing for correct setup.
- Supplied with installation materials.
- 25-year durability and leak-free warranty.

**ADD FUNCTION AND A SPLASH OF PERSONALITY WITH A TOUCH OF GLASS.**



Glass shelves and accessories are available individually.

10mm toughened safety glass with polished edges secured with matt blocks as shown.