

# linea quattro | shower system specifications

## SHOWER BASE

- Structurally solid one-piece reinforced fiberglass composite shower base – already 100% waterproof.
- Fits into a timber floor to achieve level access shower entry. Can also be placed on an existing floor or concrete slab to achieve low step entry.
- Integrated channel drain (at rear or side).
- Ready-to-tile surface – accepts a wide range of tile adhesives.
- Single slope to drain with guaranteed 1:80 fall.
- Minimum 70mm high upstand – for secure connection to wall membrane.
- Factory-fitted glass receiver channels on base.
- Base underside adhesive supplied (for fixing to floor).
- Weight: 16kg/m<sup>2</sup>.
- 25-year leak-free and durability warranty.

## CHANNEL DRAIN/ WASTE FITTING

- 50mm hi-flow waste outlet in centre position of channel drain.
- Waste is mechanically secured to base and is fitted and accessed from the top.
- Stainless steel removable grate for channel drain in plain, slotted and tile-over versions.

## BASE & WALL CHANNELS

- Base glazing channels are factory-fitted and integral with shower base.
- Base & wall glazing channels accept 10mm frameless glass (or 8mm glass when supplied by Atlantis).
- Wall glazing channels supplied at 2120mm high (standard).
- Blue liquid waterproofing (applied by others).

## WATERPROOFING

ESSENTIAL: Atlantis self-adhesive reinforcement band for critical connections in internal shower corner, wall and floor (as shown).

## FULLY FRAMELESS SCREENS

- 8mm European Standard toughened safety glass screens.
- Hinged door option complete with solid stainless steel handles, solid brass soft close hinges and fixing materials.
- Sliding door option complete with solid stainless steel handle, fully adjustable s/s roller assembly and installation materials
- Walk-in fixed screen options available in most sizes.
- High strength chrome top rail brace included.
- Screens supplied at 2120mm overall height.
- 10-year product warranty.

## WATERPROOFING

The 100% waterproof Atlantis shower base and connections are compliant with the requirements of the Building Code of Australia.

The shower system is compatible with any compliant waterproofing membrane used on the walls and for the rest of the bathroom floor.

1. Shower base
2. Channel drain and stainless steel grate
3. Waste outlet - top fixed
4. Glazing channels
5. Corner connection band
6. Essential self-adhesive reinforcement bands
7. Adhesion layer
8. (Optional) EasyNiche™ accessory
9. Blue liquid waterproofing (applied by others).

